HIT-MM PLUS

en	This safety data sheet file is issued for the following production lots: 1. Version 8.X is valid for HIT-MM PLUS with a maximum expiration date of 12/2022 (see foil pack manifold) 2. Version 9.0 is valid for HIT-MM PLUS with a minimum expiration date of 01/2023 (see the foil pack manifold)
de	Diese Sicherheitsdatenblatt-Datei betrifft die folgenden Fertigungslose: 1. Version 8.X ist gültig für HIT-MM PLUS mit einem Haltbarkeitsdatum bis 12/2022 (siehe Verbindungsteil) 2. Version 9.0 ist gültig für HIT-MM PLUS mit einem Haltbarkeitsdatum ab 01/2023 (siehe Verbindungsteil)
nl	Dit veiligheidsinformatiebladbestand wordt afgegeven voor de volgende productie-lots: 1. Versie 8.X is geldig voor HIT-MM PLUS met een maximale houdbaarheidsdatum tot 12/2022 (zie foliepak verdeler) 2. Versie 9.0 is geldig voor HIT-MM PLUS met een minimale houdbaarheidsdatum tot 01/2023 (zie foliepak verdeler)
fr	Ce fichier de données de sécurité est délivré pour les lots de production suivants : 1. La version 8.X est valide pour HIT-MM PLUS avec une date d'expiration maximale de 12/2022 (voir le raccord de cartouche souple) 2. La version 9.0 est valide pour HIT-MM PLUS avec une date d'expiration maximale de 01/2023 (voir le raccord de cartouche souple)
da	Denne sikkerhedsdatabladsfil er udgivet for følgende produktions lots: 1. Version 8.X er gældende for HIT-MM PLUS med en maksimal udløbsdato d. 12/2022 (se foliepakkens manifold) 2. Version 9.0 er gældende for HIT-MM PLUS med en mindste udløbsdato d. 01/2023 (se foliepakkens manifold)
sv	Denna säkerhetsdatabladsfil har utfärdats för följande tillverkningspartier: 1. Version 8.X är giltig för HIT-MM PLUS med ett sista giltighetsdatum den 12/2022 (se folieförpackningens grenrör) 2. Version 9.0 är giltig för HIT-MM PLUS med ett första giltighetsdatum den 01/2023 (se folieförpackningens grenrör)
fi	Tämä käyttöturvallisuustiedote koskee seuraavia tuotantoeriä: 1. Versio 8.X koskee HIT-MM PLUS -tuotetta, jonka viimeinen käyttöpäivämäärä on 12/2022 tai sitä ennen (ks. foliopakkauksen taite) 2. Versio 9.0 koskee HIT-MM PLUS -tuotetta, jonka viimeinen käyttöpäivämäärä on 01/2023 tai sen jälkeen (ks. foliopakkauksen taite)
hu	Ezt a biztonsági adatlapot a következő gyártási tételekhez bocsátják ki: 1. Az 8.X változat legfeljebb 2022/12 lejárati dátummal érvényes a HIT-MM PLUS-re (lásd a fóliacsomag sokszorosított iratát) 2. Az 9.0 változat legalább 2023/01 lejárati dátummal érvényes a HIT-MM PLUS-re (lásd a fóliacsomag sokszorosított iratát)
es	Este archivo de hoja de datos de seguridad se emite para los siguientes lotes de producción: 1. Versión 8.X válida para HIT-MM PLUS con una fecha de caducidad máxima de 12/2022 (consulte el colector de láminas) 2. Versión 9.0 válida para HIT-MM PLUS con una fecha de caducidad mínima de 01/2023 (consulte el colector de láminas)
pt	Este ficheiro com ficha de dados de segurança é emitido para os seguintes lotes de produção: 1. A versão 8.X é válida para a HIT-MM PLUS com um prazo máximo de validade até 12/2022 (ver as diversas embalagens) 2. A versão 9.0 é válida para a HIT-MM PLUS com um prazo mínimo de validade até 01/2023 (ver as diversas embalagens)
it	Questo file della scheda tecnica di sicurezza è rilasciato per i seguenti lotti di produzione: 1. La versione 8.X è valida per HIT-MM PLUS con data di scadenza massima 12/2022 (vedere la giunzione della confezione) 2. La versione 9.0 è valida per HIT-MM PLUS con data di scadenza minima 01/2023 (vedere la giunzione della confezione)
pl	Ten plik arkusza danych bezpieczeństwa jest wydany dla następujących części produkcyjnych: 1. Wersja 8.X obowiązuje w przypadku HIT-MM PLUS z maksymalnym dniem rozpoczęcia pracy 12/2022 (patrz opakowanie foliowe) 2. Wersja 9.0 obowiązuje w przypadku HIT-MM PLUS z minimalnym dniem rozpoczęcia pracy 01/2023 (patrz opakowanie foliowe)
ru	Этот файл сертификата безопасности предоставлен для следующих партий продукции: 1. Версия 8.X действительна для HIT-MM PLUS с максимальным сроком годности до 12.2022 г. (см. присоединительную часть на капсуле) 2. Версия 9.0 действительна HIT-MM PLUS с минимальным сроком годности до 01.2023 г. (см. присоединительную часть на капсуле)
el	Το παρόν δελτίο δεδομένων ασφάλειας εκδίδεται για τις ακόλουθες παρτίδες παραγωγής: 1. Η έκδοση 8.X ισχύει για το HIT-MM PLUS με μέγιστη ημερομηνία λήξης τον 12/2022 (βλέπε διανομέα συσκευασίας μεμβράνης) 2. Η έκδοση 9.0 ισχύει για το HIT-MM PLUS με ελάχιστη ημερομηνία λήξης τον 01/2023 (βλέπε τον διανομέα της συσκευασίας μεμβράνης)
cs	Tento soubor s bezpečnostním listem je vystaven pro tyto výrobní závody 1. Verze 8.X je platná pro HIT-MM PLUS s maximálním datem expirace 12/2022 (viz fólie balení) 2. Verze 9.0 je platná pro HIT-MM PLUS s minimálním datem expirace 01/2023 (viz fólie balení)
bg	Този информационен лист за безопасност се публикува за следните производствени партиди: 1. Версия 8.X е валидна за HIT-MM PLUS с максимален срок на валидност до 12.2022 г. (вж. фолийна опаковка за колектор) 2. Версия 9.0 е валидна за HIT-MM PLUS с минимален срок на изтичане 01.2023 г. (вж. фолийна опаковка за колектор)
lv	Šo drošības datu lapa ir izsniegta šādām ražojumu partijām: 1. Versija 8.X ir derīga izstrādājumam HIT-MM PLUS, kura maksimālais derīguma termiņš ir 2022. gada maijs (skatīt folija iepakojuma kolektoru) 2. Versija 9.0 ir derīga izstrādājumam HIT-MM PLUS, kura minimālais derīguma termiņš ir 2023. gada jūnijs (skatīt folija iepakojuma kolektoru)
lt	Šis saugos duomenų lapo failas išduodamas šioms gamybos partijoms: 1. 8.X versija galioja HIT-MM PLUS, kurios maksimali galiojimo data – 2022-12 (žr. folinių pakuočių rinkinį) 2. 9.0 versija galioja HIT-MM PLUS, kurios minimali galiojimo data – 2023-01 (žr. folinių pakuočių rinkinį)
sk	Tento súbor bezpečnostných údajov sa vydáva pre tieto výrobné šarže: 1. Verzia 8.X je platná pre HIT-MM PLUS s maximálnym dátumom exspirácie 12/2022 (pozrite si údaj na fólii balenia) 2. Verzia 9.0 je platná pre HIT-MM PLUS s minimálnym dátumom exspirácie 01/2023 (pozrite si údaj na fólii balenia)
sl	Datoteka z varnostnim listom je izdana za naslednje proizvodne serije: 1. Različica 8.X je veljavna za izdelek HIT-MM PLUS z maksimalnim datumom poteka veljavnosti: 12/2022 (glejte pakiranje) 2. Različica 9.0 je veljavna za izdelek HIT-MM PLUS z minimalnim datumom poteka veljavnosti: 01/2023 (glejte pakiranje)

HIT-MM PLUS

et	See ohutuskaardi fail on välja antud järgmistele tootepartiidele: 1. Versioon 8.X kehtib tootele HIT-MM PLUS viimase säilimiskuupäevaga 12/2022 (vt fooliumpakendi hargnemiskohta) 2. Versioon 9.0 kehtib tootele HIT-MM PLUS esimese säilimiskuupäevaga 01/2023 (vt fooliumpakendi hargnemiskohta)
ro	Acest fișier cu date tehnice de securitate este emis pentru următoarele locuri de producție: 1. Versiunea 8.X este valabilă pentru HIT-MM PLUS cu data maximă de expirare 12/2022 (a se vedea racordul pentru cartușe din folie) 2. Versiunea 9.0 este valabilă pentru HIT-MM PLUS cu data minimă de expirare 01/2023 (a se vedea racordul pentru cartușe din folie)
hr	Ovaj sigurnosno-tehnički list izdaje se za sljedeće proizvodne serije: 1. Verzija 8.X vrijedi za HIT-MM PLUS s maksimalnim rokom trajanja do 12/2022 (vidjeti razvodnik iz folije) 2. Verzija 9.0 vrijedi za HIT-MM PLUS s minimalnim rokom trajanja do 01/2023 (vidjeti razvodnik iz folije)
tr	Bu güvenlik bilgi formu dosyası aşağıdaki üretim partileri için hazırlanmıştır: 1. Versiyon 8.X, maksimum son kullanma tarihi 12/2022 olan HIT-MM PLUS için geçerlidir (bkz. folyo paketi manifoldu) 2. Versiyon 9.0, inimumm son kullanma tarihi 01/2023 olan HIT-MM PLUS için geçerlidir (bkz. folyo paketi manifoldu)
uk	Цей файл сертифіката безпеки надано для наступних партій продукції: 1. Версія 8.X дійсна для HIT-MM PLUS з максимальним терміном придатності до 12.2022 р. (див. приєднувальну частину на капсулі) 2. Версія 9.0 дійсна для HIT-MM PLUS з мінімальним терміном придатності до 01.2023 р. (див. приєднувальну частину на капсулі)
zh	**本安全数据表文件**针对以下生产批次发布： 1. **版本** 8.X 对 HIT-MM PLUS **有效，最**长失效日期为 2022 **年** 12 **月**（**参**见箔包装歧管 ） 2. **版本** 9.0 对 HIT-MM PLUS **有效，最短失效日期**为 2023 **年** 1 **月**（**参**见箔包装歧管）
ar	يتم إصدار ملف صحيفة بيانات السلامة لتشغيلات الإنتاج التالية: 1. الإصدار 8.X صالح لـ HIT-MM PLUS بحد أقصى لتاريخ انتهاء الصلاحية هو 2022/12 (انظر العبوة المصنوعة من رقائق الألومنيوم) 2. الإصدار 9.0 صالح لـ HIT-MM PLUS على الأقل لتاريخ انتهاء الصلاحية هو 2023/1 (انظر العبوة المصنوعة من رقائق الألومنيوم)
ja	**この安全性データシートファイルは、次の生産ロット用に発行されています**： 1. **バージョン** 8.X **は、有効期限が最大** 2022 **年** 12 **月までの** HIT-MM PLUS **に対して有効です** (**フォイルパック連結部に表示**) 2. **バージョン** 9.0 **は、有効期限が** 2023 **年** 1 **月以降の** HIT-MM PLUS **に対して有効です** (**フォイルパック連結部に表示**)
sr	Datoteka bezbednosnog lista se izdaje za sledeće proizvodne serije: 1. Verzija 8.X je dostupna za HIT-MM PLUS sa maksimalnim datumom isteka 12/2022 (pogledajte ivicu pakovanja od folije) 2. Verzija 9.0 je dostupna za HIT-MM PLUS sa minimalnim datumom isteka 01/2023 (pogledajte ivicu pakovanja od folije)
ms	Fail helaian data keselamatan ini dikeluarkan untuk lot pengeluaran yang berikut: 1. Versi 8.X adalah sah untuk HIT-MM PLUS dengan tarikh tamat tempoh maksimum pada 12/2022 (lihat manifold pek kerajang) 2. Versi 9.0 adalah sah untuk HIT-MM PLUS dengan tarikh tamat tempoh minimum pada 01/2023 (lihat manifold pek kerajang)
ko	본 안전보건자료는 다음 제품 로트에 대해 발급되었습니다. 1. 버전 8.X(은)는 HIT-MM PLUS에 대해 유효하며, 최대 만료 기한은 2022년 12월입니다(호일 팩 매니폴드 참조) 2. 버전 9.0(은)는 HIT-MM PLUS에 대해 유효하며, 최소 만료 기한은 2023년 1월입니다(호일 팩 매니폴드 참조)
id	File lembar data keselamatan ini diterbitkan untuk lot produksi berikut: 1. Versi 8.X berlaku untuk HIT-MM PLUS dengan tanggal kedaluwarsa maksimum 12/2022 (lihat foil pack manifold) 2. Versi 9.0 berlaku untuk HIT-MM PLUS dengan tanggal kedaluwarsa minimum 01/2023 (lihat foil pack manifold)
he	קובץ גיליון נתוני בטיחות זה מונפק עבור מגרשי הייצור הבאים: 1. גרסה 8.X תקפה ל-HIT-MM PLUS עם תאריך תפוגה מקסימלי של 12/2022 (ראה יריעת foil pack) 2. גרסה 9.0 תקפה ל-HIT-MM PLUS עם תאריך תפוגה מינימלי של 01/2023 (ראה יריעת foil pack)
th	แผ่นข้อมูลด้านความปลอดภัยนี้ที่ได้จัดทำสำหรับล็อตการผลิตดังต่อไปนี้: 1. เวอร์ชั่น 8.X ใช้ได้กับ HIT-MM PLUS ที่มีวันหมดอายุไม่เกิน 12/2022 (โปรดดูแผ่นพับห่อฟอยล์) 2. เวอร์ชั่น 9.0 ใช้ได้กับ HIT-MM PLUS ที่มีวันหมดอายุขั้นต่ำ 01/2023 (โปรดดูแผ่นพับห่อฟอยล์)
vi	Tệp bảng dữ liệu an toàn này được phát hành cho các lô sản xuất sau: 1. Phiên bản 8.X hợp lệ cho HIT-MM PLUS với ngày hết hạn tối đa là 12/2022 (xem ống keo cấy thép) 2. Phiên bản 9.0 hợp lệ cho HIT-MM PLUS với ngày hết hạn tối thiểu là 01/2023 (xem ống keo cấy thép)
zh tw	**下列生**產批次將獲核發本安全資料表檔案： 1. 8.X **版適用於** HIT-MM PLUS，**最長到期日** 12/2022 (**請見鋁箔包打字紙**) 2. 9.0 **版適用於** HIT-MM PLUS，**最短到期日** 01/2023 (**請見鋁箔包打字紙**)
kk	Бұл қауіпсіздік паспорты мына өндірістік партиялар үшін шығарылады: 1. 8.X нұсқасы жарамдылық мерзімі көп уақытты (12/2022) қамтитын HIT-MM PLUS үшін жарамды (жұқалтыр қаптаманы қараңыз) 2. 9.0 нұсқасы жарамдылық мерзімі аз уақытты (01/2023) қамтитын HIT-MM PLUS үшін жарамды (жұқалтыр қаптаманы қараңыз)

Hilti HIT-MM PLUS 330/1
Hilti HIT-MM PLUS 500/1
Hilti HIT-MM PLUS 330/2
Hilti HIT-MM PLUS 500/2

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

Issue date: 24/09/2021 Revision date: 24/09/2021 Supersedes: 14/04/2021 Version: 9.0

SECTION 1: Identification

1.1. GHS Product identifier

Product form	Mixture
Product name	Hilti HIT-MM PLUS 330/1 Hilti HIT-MM PLUS 500/1 Hilti HIT-MM PLUS 330/2 Hilti HIT-MM PLUS 500/2
UN-No. (ADR)	3077
Product code	BU Anchor

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture	Composite mortar component for fasteners in the construction industry
Recommended uses and restrictions	For professional users only

1.4. Supplier's details

Supplier

Hilti Emirates L.L.C.
Dubai Investment Park
P.O. Box 11051
Dubai - United Arab Emirates
T +971 800 44584 - F +971 4 885 4405

Department issuing data specification sheet

Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
86916 Kaufering - Deutschland
T +49 8191 906876

1.5. Emergency phone number

Emergency number

Schweizerisches Toxikologisches Informationszentrum – 24h Service
+41 44 251 51 51 (international)
+971 4 8019694
800-Hilti (44584) (Toll free)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to the United Nations GHS

Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment — Acute Hazard, Category 1	H400

Hazardous to the aquatic environment — Chronic Hazard, Category 1	H410

Full text of H-statements: see section 16

2.2. GHS Label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS UN)

GHS07 GHS09

Signal word (GHS UN): Warning

Hazardous ingredients: dibenzoyl peroxide; 2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester; 2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol

Hazard statements (GHS UN):
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H410 - Very toxic to aquatic life with long lasting effects

Precautionary statements (GHS UN):
P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice, medical attention.
P337+P313 - If eye irritation persists: Get medical advice, medical attention.
P302+P352 - IF ON SKIN: Wash with plenty of water.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

A Name	Product identifier	%	Classification according to the United Nations GHS
Quartz (SiO2)	(CAS-No.) 14808-60-7	25 – 40	Specific target organ toxicity — Repeated exposure, Category 1, H372
Cement, alumina	(CAS-No.) 65997-16-2	10 – 25	Not classified
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol	(CAS-No.) 27813-02-1	10 – 25	Flammable liquids Not classified Acute toxicity (oral) Not classified Serious eye damage/eye irritation, Category 2A, H319 Skin sensitisation, Category 1, H317 Hazardous to the aquatic environment — Acute Hazard, Category 3, H402 Hazardous to the aquatic environment — Chronic Hazard, Category 3, H412
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester	(CAS-No.) 2082-81-7	1 – 2.5	Acute toxicity (oral) Not classified Skin sensitisation, category 1B, H317

B Name	Product identifier	%	Classification according to the United Nations GHS
Quartz (SiO2)	(CAS-No.) 14808-60-7	40 – 60	Specific target organ toxicity — Repeated exposure, Category 1, H372
Water	(CAS-No.) 7732-18-5	25 – 40	Not classified
dibenzoyl peroxide	(CAS-No.) 94-36-0	5 – 10	Organic Peroxides, Type B, H241 Serious eye damage/eye irritation, Category 2A, H319 Skin sensitisation, Category 1, H317 Hazardous to the aquatic environment — Acute Hazard, Category 1, H400 (M=10) Hazardous to the aquatic environment — Chronic Hazard, Category 1, H410 (M=10)

Full text of H-statements: see section 16

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	Wash contaminated clothing before reuse. Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.
Potential adverse human health effects and symptoms	Based on available data, the classification criteria are not met.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

5.3. Special protective actions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.

6.1.1. For non-emergency personnel

Emergency procedures	Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. Store away from other materials.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures	Wash hands, forearms and face thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Keep cool. Protect from sunlight.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls	Ensure adequate ventilation.
Environmental exposure controls	Avoid release to the environment.
Consumer exposure controls	Avoid contact during pregnancy/while nursing.

Other information	Do not eat, drink or smoke during use.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection: Wear protective gloves.

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12		EN ISO 374

Eye protection: Chemical goggles or safety glasses

Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166, EN 170

Respiratory protection: Wear appropriate mask

Personal protective equipment symbol(s)

8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste
Colour	component A: grey, component B: white.
Odour	characteristic.
Odour threshold	Not available
Melting point	Not available
Freezing point	Not available
Boiling point	Not available
Flammability (solid, gas)	Non flammable.
Explosive limits	Not applicable
Lower explosive limit (LEL)	Not applicable
Upper explosive limit (UEL)	Not applicable
Flash point	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	Not available
pH	Not available
pH solution	Not available
Viscosity, kinematic (calculated value) (40 °C)	Not applicable
Partition coefficient n-octanol/water (Log Kow)	Not available

Vapour pressure	Not available
Vapour pressure at 50 °C	Not available
Density	1.6 – 1.7 g/cm³
Relative density	Not available
Relative vapour density at 20 °C	Not applicable
Solubility	Not available
Particle size	Not available
Particle size distribution	Not available
Particle shape	Not available
Particle aspect ratio	Not available
Particle specific surface area	Not available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
LD50 oral rat	10066 mg/kg
LD50 dermal rat	> 3000 mg/kg

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
LD50 oral rat	> 5000 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; >=2000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	≥ 5000 mg/kg bodyweight (Rabbit; Experimental value)

Skin corrosion/irritation	Not classified
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified
Potential adverse human health effects and symptoms	Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water	Very toxic to aquatic life.
Hazardous to the aquatic environment, short-term (acute)	Very toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	Very toxic to aquatic life with long lasting effects.

dibenzoyl peroxide (94-36-0)	
LC50 - Fish [2]	0.0602 mg/l (96h; Oncorhynchus mykiss; ECHA)
EC50 - Crustacea [1]	0.11 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	0.0711 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
NOEC (acute)	0.0316 mg/l (96h; Oncorhynchus mykiss; ECHA)
NOEC chronic fish	0.001 mg/l

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
LC50 - Other aquatic organisms [1]	9.79 mg/l
NOEC (acute)	7.51 mg/l
NOEC (chronic)	20 mg/l

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
LC50 - Fish [1]	493 mg/l (48 h; Leuciscus idus; GLP)
EC50 - Crustacea [1]	> 143 mg/l (48 h; Daphnia magna; GLP)
ErC50 algae	97.2 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
Threshold limit - Algae [1]	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)
Threshold limit - Algae [2]	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)

12.2. Persistence and degradability

HIT-MM PLUS	
Persistence and degradability	Not established.

Quartz (SiO2) (14808-60-7)	
Not rapidly degradable	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

dibenzoyl peroxide (94-36-0)	
Persistence and degradability	Readily biodegradable in water. Not established. May cause long-term adverse effects in the environment.

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Not rapidly degradable	
Biodegradation	84 %

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

HIT-MM PLUS	
Bioaccumulative potential	Not established.

Quartz (SiO2) (14808-60-7)	
Bioaccumulative potential	No bioaccumulation data available.

dibenzoyl peroxide (94-36-0)	
Partition coefficient n-octanol/water (Log Kow)	3.71
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Partition coefficient n-octanol/water (Log Kow)	3.1

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
BCF - Fish [1]	≤ 100
BCF - Fish [2]	3.2 Quantitative structure-activity relationship (QSAR)
Partition coefficient n-octanol/water (Log Kow)	0.97 (OECD 102 method)
Bioaccumulative potential	Low bioaccumulation potential (BCF < 500).

12.4. Mobility in soil

HIT-MM PLUS	
Mobility in soil	No additional information available

Quartz (SiO2) (14808-60-7)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.

dibenzoyl peroxide (94-36-0)	
Surface tension	No data available (test not performed)
Partition coefficient n-octanol/water (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Ecology - soil	Low potential for mobility in soil.

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Partition coefficient n-octanol/water (Log Koc)	1.9 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Ozone	Not classified
Other adverse effects	No additional information available
Other information	Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations	Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Ecology - waste materials	Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
14.1. UN number or ID number			
UN 3077	UN 3077	UN 3077	UN 3077
14.2. UN proper shipping name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide)	Environmentally hazardous substance, solid, n.o.s. (dibenzoyl peroxide)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide)
Transport document description			
UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide), 9, III, (-)	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide), 9, III, MARINE POLLUTANT	UN 3077 Environmentally hazardous substance, solid, n.o.s. (dibenzoyl peroxide), 9, III	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (dibenzoyl peroxide), 9, III
14.3. Transport hazard class(es)			
9	9	9	9
			
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
not restricted according ADR Special Provision SP375, IATA-DGR Special Provision A197 and IMDG-Code 2.10.2.7			

14.6. Special precautions for user

Overland transport

Classification code (ADR)	M7
Special provisions (ADR)	274, 335, 375, 601
Limited quantities (ADR)	5kg
Packing instructions (ADR)	P002, IBC08, LP02, R001
Mixed packing provisions (ADR)	MP10
Transport category (ADR)	3
Orange plates	
Tunnel restriction code (ADR)	-

Transport by sea

Special provisions (IMDG)	274, 335, 966, 967, 969
Limited quantities (IMDG)	5 kg
Packing instructions (IMDG)	LP02, P002
EmS-No. (Fire)	F-A
EmS-No. (Spillage)	S-F
Stowage category (IMDG)	A
Stowage and handling (IMDG)	SW23

Air transport

PCA packing instructions (IATA)	956
PCA max net quantity (IATA)	400kg
CAO packing instructions (IATA)	956
Special provisions (IATA)	A97, A158, A179, A197, A215

Rail transport

Special provisions (RID)	274, 335, 375, 601
Limited quantities (RID)	5kg
Packing instructions (RID)	P002, IBC08, LP02, R001

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

SECTION 16: Other information

Issue date	24/09/2021
Revision date	24/09/2021

Hilti HIT-MM PLUS 330/1
Hilti HIT-MM PLUS 500/1
Hilti HIT-MM PLUS 330/2
Hilti HIT-MM PLUS 500/2

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

Supersedes	14/04/2021
Other information	None.

Full text of H-statements:	
H241	Heating may cause a fire or explosion
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

SDS_UN_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Hilti HIT-MM PLUS 330/1
Hilti HIT-MM PLUS 500/1
Hilti HIT-MM PLUS 330/2
Hilti HIT-MM PLUS 500/2

Safety Data Sheet

according to the United Nations GHS (Rev. 4, 2011)

Issue date: 14/04/2021 Revision date: 14/04/2021 Supersedes: 03/04/2020 Version: 8.1

SECTION 1: Identification

1.1. GHS Product identifier

Product form	Mixture
Product name	HIT-MM PLUS
Product code	BU Anchor

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture	Composite mortar component for fasteners in the construction industry
Recommended uses and restrictions	For professional users only

1.4. Supplier's details

Supplier
Hilti Emira tes L.L.C.
Dubai Investment Park
P.O. Box 11051
Dubai - United Arab Emirates
T +971 800 44584 - F +971 4 885 4405
ae.contactus@hilti.com - www.hilti.ae

Department issuing data specification sheet
Hilti Entwicklungsgesellschaft mbH
Hiltistraße 6
86916 Kaufering - Deutschland
T +49 8191 906876
anchor.hse@hilti.com

1.5. Emergency phone number

Emergency number	Schweizerisches Toxikologisches Informationszentrum – 24h Service +41 44 251 51 51 (international) +971 4 8019694 800-Hilti (44584) (Toll free)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification according to the United Nations GHS

Serious eye damage/eye irritation, Category 2A	H319
Skin sensitisation, Category 1	H317
Carcinogenicity, Category 1B	H350
Hazardous to the aquatic environment — Acute Hazard, Category 1	H400
Hazardous to the aquatic environment — Chronic Hazard, Category 1	H410

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

Labelling according to the United Nations GHS

Hazard pictograms (GHS UN)

GHS07 GHS08 GHS09

Signal word (GHS UN): Danger

Hazard statements (GHS UN):
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H350 - May cause cancer
H410 - Very toxic to aquatic life with long lasting effects

Precautionary statements (GHS UN):
P280 - Wear eye protection, protective clothing, protective gloves.
P262 - Do not get in eyes, on skin, or on clothing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice, medical attention.
P337+P313 - If eye irritation persists: Get medical advice, medical attention.
P302+P352 - IF ON SKIN: Wash with plenty of water.

2.3. Other hazards which do not result in classification

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures



2-Component-foilpack, contains:
Component A: Urethane methacrylate resin, inorganic filler
Component B: Dibenzoyl peroxide, phlegmatized

A			
Name	Product identifier	%	Classification according to the United Nations GHS
Cement, alumina	(CAS-No.) 65997-16-2	10 - 25	Not classified
Aluminum oxide (Al2O3)	(CAS-No.) 1344-28-1	5 - 10	Acute toxicity (oral) Not classified Acute toxicity (inhalation:dust,mist) Not classified
Quartz (SiO2)	(CAS-No.) 14808-60-7	25 - 40	Specific target organ toxicity — Repeated exposure, Category 1, H372
1,1'-(p-tolylimino)dipropan-2-ol	(CAS-No.) 38668-48-3	0.1 - 1	Acute toxicity (oral), Category 2, H300 Serious eye damage/eye irritation, Category 2A, H319 Hazardous to the aquatic environment — Acute Hazard, Category 3, H402

			Hazardous to the aquatic environment — Chronic Hazard, Category 3, H412
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester	(CAS-No.) 2082-81-7	1 - 2.5	Acute toxicity (oral) Not classified Skin sensitisation, category 1B, H317
1,2-dihydroxybenzene	(CAS-No.) 120-80-9	0.1 - 1	Acute toxicity (oral), Category 3, H301 Acute toxicity (dermal), Category 3, H311 Skin corrosion/irritation, Category 2, H315 Serious eye damage/eye irritation, Category 1, H318 Skin sensitisation, Category 1, H317 Germ cell mutagenicity, Category 2, H341 Carcinogenicity, Category 1B, H350
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol	(CAS-No.) 27813-02-1	10 - 25	Flammable liquids Not classified Acute toxicity (oral) Not classified Serious eye damage/eye irritation, Category 2A, H319 Skin sensitisation, Category 1, H317 Hazardous to the aquatic environment — Acute Hazard, Category 3, H402 Hazardous to the aquatic environment — Chronic Hazard, Category 3, H412

B			
Name	Product identifier	%	Classification according to the United Nations GHS
Quartz (SiO2)	(CAS-No.) 14808-60-7	40 - 60	Specific target organ toxicity — Repeated exposure, Category 1, H372
dibenzoyl peroxide	(CAS-No.) 94-36-0	5 - 10	Organic Peroxides, Type B, H241 Serious eye damage/eye irritation, Category 2A, H319 Skin sensitisation, Category 1, H317 Hazardous to the aquatic environment — Acute Hazard, Category 1, H400 (M=10) Hazardous to the aquatic environment — Chronic Hazard, Category 1, H410 (M=10)
Water	(CAS-No.) 7732-18-5	25 - 40	Not classified

Full text of H-statements: see section 16

SECTION 4: First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general: Take off immediately all contaminated clothing. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact: Wash contaminated clothing before reuse. Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact: Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persists.

First-aid measures after ingestion	Rinse mouth. Get medical advice/attention. Do not induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after skin contact	May cause an allergic skin reaction.
Symptoms/effects after eye contact	May cause severe irritation.
Potential adverse human health effects and symptoms	Based on available data, the classification criteria are not met.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire	Thermal decomposition generates : Carbon dioxide. Carbon monoxide.

5.3. Special protective actions for fire-fighters

Firefighting instructions	Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	Self-contained breathing apparatus. Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	Spilled material may present a slipping hazard.

6.1.1. For non-emergency personnel

Emergency procedures	Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	Equip cleanup crew with proper protection.
Emergency procedures	Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and materials for containment and cleaning up

For containment	Collect spillage.
Methods for cleaning up	This material and its container must be disposed of in a safe way, and as per local legislation. Mechanically recover the product. Store away from other materials.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	Wear personal protective equipment. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures	Wash hands, forearms and face thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	Keep cool. Protect from sunlight.
Incompatible products	Strong bases. Strong acids.
Incompatible materials	Sources of ignition. Direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls	Ensure adequate ventilation.
Environmental exposure controls	Avoid release to the environment.
Consumer exposure controls	Avoid contact during pregnancy/while nursing.
Other information	Do not eat, drink or smoke during use.

8.3. Individual protection measures, such as personal protective equipment (PPE)

Hand protection: Wear protective gloves.

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	0,12		EN ISO 374

Eye protection: Chemical goggles or safety glasses

Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166, EN 170

Skin and body protection: Wear suitable protective clothing

Respiratory protection: Wear appropriate mask

Personal protective equipment symbol(s)

8.4. Exposure limit values for the other components

No additional information available

SECTION 9: Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	Solid
Appearance	Thixotropic paste
Colour	component A: grey, component B: white.
Odour	characteristic.
Odour threshold	Not available
Melting point	Not available
Freezing point	Not available
Boiling point	Not available
Flammability (solid, gas)	Not available
Explosive limits	Not applicable
Lower explosive limit (LEL)	Not applicable
Upper explosive limit (UEL)	Not applicable
Flash point	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	Not available
pH	Not available
pH solution	Not available
Viscosity, kinematic (calculated value) (40 °C)	Not applicable
Partition coefficient n-octanol/water (Log Kow)	Not available
Vapour pressure	Not available
Vapour pressure at 50 °C	Not available
Density	Component A: 1.65 g/cm³; component B: 1.7 g/cm³
Relative density	Not available
Relative vapour density at 20 °C	Not applicable
Solubility	Not available
Particle size	Not available
Particle size distribution	Not available
Particle shape	Not available
Particle aspect ratio	Not available
Particle specific surface area	Not available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	Not classified
Acute toxicity (dermal)	Not classified
Acute toxicity (inhalation)	Not classified

Aluminum oxide (Al2O3) (1344-28-1)	
LD50 oral rat	> 15900 mg/kg
LC50 Inhalation - Rat	7.6 mg/l
1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
LD50 oral rat	25 mg/kg
LD50 dermal rat	> 2000 mg/kg
2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
LD50 oral rat	10066 mg/kg
LD50 dermal rat	> 3000 mg/kg
1,2-dihydroxybenzene (120-80-9)	
LD50 oral rat	300 mg/kg
LD50 dermal rat	600 mg/kg
LC50 Inhalation - Rat (Vapours)	≥ 2.8 mg/l/4h
2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
LD50 oral rat	> 5000 mg/kg (Rat; OECD 401: Acute Oral Toxicity; Literature study; >=2000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	≥ 5000 mg/kg bodyweight (Rabbit; Experimental value)

Skin corrosion/irritation	Not classified
Serious eye damage/irritation	Causes serious eye irritation.
Respiratory or skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified
Carcinogenicity	May cause cancer.
Reproductive toxicity	Not classified
STOT-single exposure	Not classified
STOT-repeated exposure	Not classified
Aspiration hazard	Not classified

Potential adverse human health effects and symptoms	No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water	Very toxic to aquatic life.
Hazardous to the aquatic environment, short-term (acute)	Very toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	Very toxic to aquatic life with long lasting effects.

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
LC50 - Fish [1]	≈ 17 mg/l
LC50 - Other aquatic organisms [1]	245 mg/l
EC50 - Crustacea [1]	28.8 mg/l
NOEC (acute)	57.8 mg/l

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
LC50 - Other aquatic organisms [1]	9.79 mg/l
NOEC (acute)	7.51 mg/l
NOEC (chronic)	20 mg/l

1,2-dihydroxybenzene (120-80-9)	
LC50 - Fish [1]	9.22 mg/l
LC50 - Other aquatic organisms [1]	22 mg/l

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
LC50 - Fish [1]	493 mg/l (48 h; Leuciscus idus; GLP)
EC50 - Crustacea [1]	> 143 mg/l (48 h; Daphnia magna; GLP)
ErC50 algae	97.2 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
Threshold limit - Algae [1]	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)
Threshold limit - Algae [2]	> 97.2 mg/l (72 h; Pseudokirchneriella subcapitata; GLP)

dibenzoyl peroxide (94-36-0)	
LC50 - Fish [2]	0.0602 mg/l (96h; Oncorhynchus mykiss; ECHA)
EC50 - Crustacea [1]	0.11 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 algae	0.0711 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
NOEC (acute)	0.0316 mg/l (96h; Oncorhynchus mykiss; ECHA)
NOEC chronic fish	0.001 mg/l

12.2. Persistence and degradability

HIT-MM PLUS	
Persistence and degradability	Not established.

Aluminum oxide (Al2O3) (1344-28-1)
Not rapidly degradable

Quartz (SiO2) (14808-60-7)	
Not rapidly degradable	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Not rapidly degradable	
Biodegradation	84 %

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Not rapidly degradable	
Persistence and degradability	Readily biodegradable in water.

dibenzoyl peroxide (94-36-0)	
Persistence and degradability	Readily biodegradable in water. Not established. May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

HIT-MM PLUS	
Bioaccumulative potential	Not established.

Quartz (SiO2) (14808-60-7)	
Bioaccumulative potential	No bioaccumulation data available.

1,1'-(p-tolylimino)dipropan-2-ol (38668-48-3)	
Partition coefficient n-octanol/water (Log Pow)	2.1

2-Propenoic acid, 2-methyl-, 1,4-butanediyl ester (2082-81-7)	
Partition coefficient n-octanol/water (Log Kow)	3.1

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
BCF - Fish [1]	≤ 100
BCF - Fish [2]	3.2 Quantitative structure-activity relationship (QSAR)
Partition coefficient n-octanol/water (Log Kow)	0.97 (OECD 102 method)
Bioaccumulative potential	Low bioaccumulation potential (BCF < 500).

dibenzoyl peroxide (94-36-0)	
Partition coefficient n-octanol/water (Log Kow)	3.71
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).

12.4. Mobility in soil

HIT-MM PLUS	
Mobility in soil	No additional information available

Quartz (SiO2) (14808-60-7)	
Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.

2-Propenoic acid, 2-methyl-, monoester with 1,2-propanediol (27813-02-1)	
Partition coefficient n-octanol/water (Log Koc)	1.9 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

dibenzoyl peroxide (94-36-0)	
Surface tension	No data available (test not performed)
Partition coefficient n-octanol/water (Log Koc)	3.8 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value)
Ecology - soil	Low potential for mobility in soil.

12.5. Other adverse effects

Ozone	Not classified
Other adverse effects	No additional information available

Other information	Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations	After curing, the product can be disposed of with household waste. . Full or only partially emptied cartridges must be disposed of as special waste in accordance with official regulations. Packaging contaminated by the product : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID /

ADR	IMDG	IATA	RID
14.1. UN number or ID number			
Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name			
Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)			
Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group			
Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards			
Not regulated	Not regulated	Not regulated	Not regulated
Environmentally hazardous substances derogation applies (quantity of liquids ≤ 5 litres or net mass of solids ≤ 5 kg). The environmentally hazardous substance mark is therefore not required, as stated in the ADR regulation, section 5.2.1.8.1.			
No supplementary information available			

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations specific for the product in question

No additional information available

SECTION 16: Other information

Issue date	14/04/2021
Revision date	14/04/2021
Supersedes	03/04/2020
Other information	None.

Full text of H-statements:	
H241	Heating may cause a fire or explosion
H300	Fatal if swallowed
H301	Toxic if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H341	Suspected of causing genetic defects
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

SDS_UN_Hilti

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.